

Public-data File 85-67

HYDROLOGIC RECONNAISSANCE OF THE
STONY RIVER BASIN, ALASKA, 1983-84

By

E.J. Collazzi

Alaska Division of
Geological and Geophysical Surveys

December 1985

THIS REPORT HAS NOT BEEN REVIEWED FOR
TECHNICAL CONTENT (EXCEPT AS NOTED IN
TEXT) OR FOR CONFORMITY TO THE
EDITORIAL STANDARDS OF DGGS.

794 University Avenue, Basement
Fairbanks, Alaska 99701

TABLE OF CONTENTS

	<u>Page</u>
Project description.....	1
Explanation of graphics.....	.2
Acknowledgements3
References cited.....	4

LIST OF GRAPHICS

Figure 1	Index of USGS topographic maps
Figure 2	Generalized physiography
Figure 3	River profiles
Figure 4	Channel cross-sections
Table 1	Summary of observed data
Table 2	Summary of calculated data
Table 3	Water-quality data

HYDROLOGIC RECONNAISSANCE OF THE
STONY RIVER BASIN, ALASKA, 1983-84

b y E.J. Collazzi

Alaska DGGs personnel reconnoitered the Stony River basin in southwestern Alaska in August 1983 and March 1984 to collect hydrologic data to describe the flow characteristics and quality of the surface water in the basin under both summer (high-flow) and winter (low-flow) conditions.

The 180-mi-long Stony River drains approximately 3,300 mi² of southwestern Alaska. The river drops 3,750 ft from its glacial headwaters in the Alaska Range to its confluence with the Kuskokwim River. Poorly-drained soils with a peaty surface layer over a shallow permafrost table predominate within the basin (Selkregg, 1976). Spruce-hardwood forest is the dominant vegetation, with alpine tundra at the higher elevations. Bedrock is exposed in the upper basin.

The Stony River basin straddles parts of the Holitna Lowland, Nushagak-Big River Hills and Southern Alaska Range as described by Wahrhaftig (1965). The Stony River is one of several large, braided glacial streams which rise from glaciers in the Alaska Range and flow across the moraine-mantled lowlands. Pleistocene alluvial deposits border the lower river, and Permian limestone and volcanic rock occur in the Lime Hills, conspicuous isolated steep-sided ridges which rise to an altitude of 1000-2000 ft. Mountains in the basin consist of Tertiary and Cretaceous granitic rocks, Cretaceous and Jurassic sedimentary and volcanic rocks, and pre-Cretaceous sedimentary, volcanic and igneous rocks (Beikman, 1974). Numerous morainal and thaw lakes occur throughout the lowland.

The Stony River basin lies within the continental climatic zone of Alaska, characterised by cold winters and hot summers. The weather station at Sparrevohn, on the southwest margin of the basin, records a mean summer temperature of 40° to 61°F, mean winter temperature of 0° to 20°F, and extremes of -47°F and 82°F over a 10-year period. Average annual precipitation at the station is 21 in. including 81 in. of snow (Selkregg, 1976). Regional variations should be expected within the basin.

DGGs personnel floated the Necons River from Two Lakes to its confluence with

the Stony River, then the Stony River to its mouth in August 1983 and obtained discharge, water-quality and stream-channel measurements at 11 sites. In March 1984 the sites were revisited by helicopter.

Information in this report can be used to assess runoff and baseflow conditions of the river system and to estimate the year-round regimen of this southwestern Alaska river basin.

EXPLANATION OF GRAPHICS

Figure 1 is an index of U.S. Geological Survey (USGS) 1:250,000- and 1:63,360-scale topographic maps of the Stony River basin.

Figure 2 shows the generalized physiography of the basin superimposed over a diagrammatic representation of the riverine system.

Figure 3 is a profile of the Stony River and selected tributaries compiled from USGS 1:63,360-scale topographic maps. Comparative gradients along river segments and the position of tributaries and data-collection sites are shown.

Figure 4 contains a channel cross section of each data-collection site. Cross sections were developed from survey measurements taken during the August 1983 reconnaissance. Bankfull channel stage was determined from the flood-plain surface and the Lower Limits of permanent vegetation (Childers and Kernodle, 1983); maximum-evident-flood (MEF) stage was extrapolated from high-water marks found on the riverbanks.

Table I is a summary of the channel geometry and discharge measurements taken during the two reconnaissance trips and the calculated unit runoff based on these measurements. Unit runoff, obtained by dividing stream discharge by drainage area, can be used to compare seasonal water yields in a basin or subbasin (Childers and Kernodle, 1983).

Table 2 contains calculations based on the observed data. From the channel cross sections, the approximate discharge **for** bankfull and MEF conditions are calculated with the simplified slope-area method (Riggs, 1979). The bankfull discharge indicates the maximum amount of flow that may be expected without flooding, and the MEF discharge indicates the maximum instantaneous peak discharge at the site in recent years (Childers and Kernodt, 1983). Drainage-basin characteristics are used to calculate predicted 2-yr and 50-yr floods using Lamke's (1979) method. (A 2-yr flood has a 50 percent chance of being exceeded in a particular year, whereas a 50-yr flood has a 2 percent chance of being exceeded; these values are based on multiple regression analysis of streamflow records, which are very scanty in Alaska.) The Froude number is a mathematical relationship between mean velocity, mean depth, and the gravitational constant and is used to compare states of flow at the sites. (In a rectangular channel, flow is **tranquil** if the Froude number is less than 1.0 and is rapid if greater than 1.0 [Dalrymple and Benson, 1968]). Observed summer stage was used as a basis in calculating discharge **using** the simplified slope-area method and may be compared to the actual discharge **values** in Table 1. Site-specific conditions, such as local variations in slope due to a nonideal channel reach, cause discrepancies between calculated and measured discharge values.

Table 3 is a summary of water-quality data gathered at all sites during **the 1983** and 1984 reconnaissance trips.

ACKNOWLEDGEMENTS

The author thanks Roy Ireland, Stan **Carrick** and Steve **Mack** of DGGS for their assistance in gathering **data** for **this** report, and Wyatt G. Gilbert of **DGGS** for his thoughtful review.

REFERENCES CITED

- Beikman, H.M., 1974, Preliminary geologic map of the southwest quadrant of Alaska: U.S. Geological Survey Miscellaneous Field Studies Map MF-611, 2 sheets.
- Childers, J.M., and Kernodle, D.R., 1983, Reconnaissance of surface-water resources in the Kobuk River basin, Alaska, 1979-80: U.S. Geological Survey Water-resources; Investigations Report 83-4027, 35 p.
- Dalrymple, T., and Benson, M.A., 1968, Measurement of peak discharge by the slope-area method: U.S. Geological Survey, Techniques of water-resources investigations, Book 3, Chapter A2, 12 p.
- Lamke, R.D., 1979, Flood characteristics of Alaskan streams: U.S. Geological Survey Water-resources Investigations Report 78-129, 61 p.
- Riggs, H.C., 1979, A simplified slope-area method for estimating flood discharge in natural channels: U.S. Geological Survey Journal of Research, v.4, 1, 285-291.
- Selkregg, L.L., 1976, Alaska regional profiles--Southwest region: Anchorage, University of Alaska Arctic Environmental Information and Data Center, 313 p.
- Wahrhaftig, C., 1965, Physiographic divisions of Alaska: U.S. Geological Survey Professional Paper 482, 52 p.




Figure 1. Index of U.S. Geological Survey topographic maps by quadrangle for the Stony River basin, Alaska.




Figure 2. Generalized physiography, Stony River basin, Alaska.




Figure 4. Channel cross-sections, Stony River basin, Alaska, August 1983.




Figure 3. Profile of Stony River and selected tributaries, Alaska.

Table 1. Summary of observed discharge and cross-sectional data, Stony River basin, Alaska, 1983-84.

Data collection site	Slope (ft/ft)	Cross-sectional area-ft ²		Water-surface width (ft)		Mean depth (ft)		Maximum depth (ft)		Mean velocity (fps)		Maximum velocity (fps)		Discharge (cfs)		Unit runoff (cfs/mi ²)	
		winter ^a	summer	winter	summer	winter	summer	winter	summer	winter	summer	winter	summer	winter	summer	winter	summer
1. Necons River	0.0018	138	412	160	150	0.9	2.8	2.0	5.2	1.6	2.5	2.5	4.0	201	1,290	0.56	3.58
2. Stony River below Necons River	0.0008	559	1,020	152	287	3.7	3.8	6.1	7.7	1.0	2.8	1.6	4.6	514	3,140	0.73	4.49
3. Telaquana River	0.0001	266	827	217	282	1.2	3.3	2.8	6.8	0.9	1.3	1.2	2.2	212	1,420	0.48	3.19
4. Stony River below Telaquana River	0.0004	425	2,130	445	460	1.0	4.4	3.7	7.0	1.2	2.1	2.3	3.2	479	5,050	0.40	4.21
5. Rock Creek	0.0048	15	67	21	59	0.7	1.1	1.4	1.8	1.4	3.3	2.1	4.1	21	218	0.32	3.35
6. Little Underhill Creek	b																
7. Can Creek	0.0024	21	88	27	59	0.8	1.5	1.5	2.2	2.7	2.0	4.0	3.0	51	179	0.28	0.99
8. Stony River 4 mi above Lime Village	0.0014	654	1,590	355	368	1.8	3.7	3.5	7.0	2.3	5.2	4.0	5.6	1,360	8,260	0.64	3.90
9. Stink River		40	274	114	108	0.4	2.7	2.3	4.0	0.2	0.4	0.3	0.9	6	142	0.02	0.37
10. Stony River below Stink River	0.0008	510	1,740	350	420	1.5	3.9	4.0	7.5	1.7	3.9	2.5	4.8	805	6,860	0.28	2.37
11. Stony River above Kuskokwim River	0.0005	1,110	1,880	235	420	4.1	3.9	12.1	6.0	1.0	2.8	1.7	4.5	1,010	7,150	0.31	2.20

^a 'Winter' refers to reconnaissance of March 1984; 'summer' to August 1983.

^b No measurements made.

Table 2. Summary of calculated discharge and cross-sectional data, Stony River basin, Alaska, 1983-84.

Data collection site	Calculated bankfull characteristics						Calculated MEF characteristics			Drainage basin characteristics					Predicted flood		Froude number	Calculated slope-
	Cross-sectional area (ft ²)	Water-surface width (ft)	Mean depth (ft)	Maximum depth (ft)	Mean velocity (fs)	Discharge (cfs)	Cross-sectional area (ft ²)	Discharge (cfs)	Unit runoff (cfs/mi)	Area (mi ²)	Mean annual precipitation (in.)	Mean minimum temperature, January (°F)	% of basin forested	% of basin under lakes	Q ₂ (cfs) 2-year flood	Q ₅₀ (cfs) 50-year flood	number (Aug. 1981 flow)	area discharge at observed August 1983 stage (cfs)
1. Necons River	780	235	3.3	10.2	5.6	4,500	780	4,500	12.50	360	22	-8	30	3	2,450	6,360	0.26	1,930
2. Stony River below Necons River	2,600	510	5.1	12.8	6.3	16,400	4,030	29,500	42.14	700	22	-3	10	1	4,990	11,900	0.25	4,740
3. Telaquana River	1,440	335	4.3	9.8	2.1	2,960	1,870	4,180	9.39	445	22	-6	65	8	2,300	5,740	0.13	1,410
4. Stony River below Telaquana River	2,960	495	6.0	10.0	5.3	14,700	4,500	25,600	21.33	1,200	22	-8	30	4	6,713	14,900	0.18	9,450
5. Rock Creek	155	95	1.6	3.5	4.7	130	250	1,370	21.08	65	22	-3	55	0	590	1,930	0.56	239
6. Little Underhill Creek	^a									285	22	-8	60	2	1,890	5,040		
7. Can Creek	160	105	1.5	7.2	3.8	605	310	1,460	8.11	180	22	-8	20	1	1,550	4,430	0.29	273
8. Stony River 4 mi above Lime Village	2,890	635	4.6	9.2	8.1	23,500	6,490	68,800	32.45	2,120	22	-8	55	3	11,800	24,200	0.48	10,600
9. Stink River										385	22	-8	50	7	2,130	5,430	0.04	
10. Stony River below Stink River	3,880	770	5.0	13.2	7.2	28,000	7,140	63,000	21.72	2,900	22	-8	60	4	14,900	29,400	0.35	9,640
11. Stony River above Kuskokwim River	3,890	450	8.6	9.2	6.0	23,200	5,580	17,500	11.54	3,250	22	-8	55	4	16,800	32,700	0.25	8,840

^a No measurements made

Table 3. Field water quality at data collection sites, Stony River basin, Alaska, 1983-84.

Data	collection	site	water temperature (°C)		Specific conductance (umhos/cm @ 25°C)		Dissolved oxygen (mg/l)		pH	
			winter*	summer	winter	summer	winter	summer	winter	summer
1.	Necons	River	-0.1	11.0	81	58	13.0	^b	6.7	
2.	Stony River below	Necons River	-0.2	10.0	84	49	12.3	12.2	6.0	
3.	Tclaquana	River	-0.2	12.0	73	54	12.5		5.6	
4.	Stony River below	Telaquana River	-0.2	12.0	80	56	11.8		6.0	-
5.	Rock	Creek	-0.2	6.8	53	32	13.1		6.6	-
6.	Little Under-hill	Creek		7.0	-	32	-	-	-	-
7.	Can	Creek	-0.2	11.5	81	75	11.9		5.5	-
8.	Stony River 4 mi	above Lime Village	-0.2	10.0	75	86	11.8		6.2	
9.	Stink	River	-0.2	12.0	233	100	0.0		6.2	-
10.	Stony River below	Stink River	-0.2	11.2	95	72	10.8	-	5.9	
11.	Stony River above	Ruskokwim River	-0.1	12.0	41	58	10.0		5.6	-

^a 'Winter' refers to reconnaissance of March 1984; 'summer' to August 1983.

^b No measurements made.